



Exacting Standards, Just Like yours, since 1948

Project

Item Number

Quantity

SL160 / SL200 / SL280



## SL160 / SL200 / SL280 SILVERLINE Spiral Mixers

### Models:

- SL160:** 243 quart (230 Liter) Spiral Mixer
- SL200:** 306 quart (290 Liter) Spiral Mixer
- SL280:** 444 quart (420 Liter) Spiral Mixer



SILVERLINE  
Spiral Mixer

### Features:

- Stainless steel bowl, spiral dough hook, and shaft
- Separate bowl and agitator motors
- Has two speeds and reverse function
- Control board has separate timers for 1st and 2nd speed
- Mixer is equipped with built in castors and leveling feet for easy positioning and set-up
- Safety switches protect operator from injury if bowl lid is open.
- Powerful belt drive provides low vibration, low noise, and economical maintenance for years of reliable service

### Standard Accessories:

- Stainless steel bowl
- Stainless steel dough Hook

### Optional Accessories:

Univex Corporation

Dough Capacity:  
**SL160:** 1353lb (160kg)  
**SL200:** 441lb (200kg)  
**SL280:** 617lb (280kg)

Speeds:  
**Dough hook:**  
 1st speed: 95rpm  
 2nd speed: 190rpm  
**Bowl:**  
 1st speed: 15rpm

### Warranty:

- One year, on-site parts and labor

#### Warranty Details

The SILVERLINE Spiral mixers carries a one-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins on the date of the purchase and, provided the unit is used in accordance with our instructions, is in full effect for one year from that date. Any work performed under this warranty must be performed between the hours of 8am and 5pm Monday through Friday. Univex will not pay for overtime charges for work performed other than during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Univex shall not be liable for any consequential compensatory, incidental, or special damages. Contact the Univex service department for any warranty claims.



Univex Corporation  
[www.Univexcorp.com](http://www.Univexcorp.com)

3 Old Rockingham Rd  
 Salem, NH 03079  
 United States of America

Telephone (800) 258-6358  
 Intl Tel. (603) 8936191  
 Fax (800) 356-5614  
 Intl Fax (603) 8931249



*Exacting Standards, Just Like yours, since 1948*

# SILVERLINE Spiral Mixer

SL160 / SL200 / SL280



## Dimensions:

	SL160	SL200	SL280
<b>A:</b>	35.8" (910mm)	35.8" (910mm)	41.3" (1050mm)
<b>B:</b>	59.1" (1500mm)	61.8" (1570mm)	65.7" (1670mm)
<b>C:</b>	63" (1600mm)	63" (1600mm)	63" (1600mm)
<b>D:</b>	80.7" (2050mm)	82.7" (2100mm)	84.6" (2150mm)

- A:** Total mixer width including bowl diameter.
- B:** Total mixer depth
- C:** Mixer Height
- D:** Mixer height including safety guard/lid fully open

Motor:  
Spiral:  
**SL160:** 15HP, 52.5A, 11KW  
**SL200:** 15HP, 52.5A, 11KW  
**SL280:** 17.7HP, 63.5A, 13.2KW

Bowl:  
**SL160:** 1HP, 4.48A, .75KW  
**SL200:** 1HP, 4.48A, .75KW  
**SL280:** 1HP, 4.48A, .75KW

Electrical: 220V/60Hz/3P (Contact factory for alternate voltages)

Controls: Control panel with digital timers. Separate timers for high and low speed. Security key for manual use. Bowl reverse direction switch.

Transmission: Heavy duty low noise, low vibration belt drive

Bowl Guard: Swings open for full access to bowl. Guard must be closed for mixer operation

## Shipping Information:

	SL160	SL200	SL280
<b>Freight Class:</b>	85	85	85
<b>Net Weight:</b>	1521lb (690kg)	1653lb (750kg)	1830lb (830kg)
<b>Shipping Weight:</b>	1631lb (740kg)	1764lb (800kg)	1940lb (880kg)

## Shipping Box Dimensions:

	GL50	GL80	GL120
<b>Height:</b>	69"(1760mm)	69"(1760mm)	69"(1760mm)
<b>Width:</b>	41"(1050mm)	51"(1300mm)	55"(1400mm)
<b>Depth:</b>	63"(1600mm)	79"(2000mm)	87"(2200mm)
<b>Cubic Measure:</b>	160:104ft <sup>3</sup> (3M <sup>3</sup> )	200:162ft <sup>3</sup> (4.6M <sup>3</sup> )	280:192ft <sup>3</sup> (5.4M <sup>3</sup> )



**Univex Corporation**  
[www.Univexcorp.com](http://www.Univexcorp.com)

3 Old Rockingham Rd  
Salem, NH 03079  
United States of America

Telephone (800) 258-6358  
Intl Tel. (603) 8936191  
Fax (800) 356-5614  
Intl Fax (603) 8931249