



Exacting Standards, Just Like yours, since 1948

Project

Item Number

Quantity

SL50 / SL60 PLUS /
SL80 / SL120



SL50 / SL60 PLUS / SL80 / SL120 SILVERLINE Spiral Mixers

Models:

- SL50:** 70 quart (68 Liter) Spiral Mixer
- SL60 Plus:** 120 quart (115 Liter) Spiral Mixer
- SL80:** 135 quart (130 Liter) Spiral Mixer
- SL120:** 180 quart (170 Liter) Spiral Mixer



SILVERLINE
Spiral Mixer

Features:

- Stainless steel bowl, spiral dough hook, and shaft
- Separate bowl and agitator motors
- Has two speeds and reverse function
- Control board has separate timers for 1st and 2nd speed
- Mixer is equipped with built in castors and leveling feet for easy positioning and set-up
- Safety switches protect operator from injury if bowl lid is open.
- Powerful belt drive provides low vibration, low noise, and economical maintenance for years of reliable service

Standard Accessories:

- Stainless steel bowl
- Stainless steel dough Hook

Optional Accessories:

Warranty:

- One year, on-site parts and labor

Univex Corporation

Dough Capacity:
SL50: 110lb (50kg)
SL60Plus: 132lb (60kg)
SL80: 176lb (80kg)
SL120: 265lb (120kg)

Speeds: Dough
hook:
1st speed: 95rpm
2nd speed: 190rpm
Bowl:
1st speed: 8rpm
2nd speed: 16rpm

Warranty Details

The SILVERLINE Spiral mixers carries a one-year, on-site parts and labor warranty against any flaws in materials and workmanship. This period begins on the date of the purchase and, provided the unit is used in accordance with our instructions, is in full effect for one year from that date. Any work performed under this warranty must be performed between the hours of 8am and 5pm Monday through Friday. Univex will not pay for overtime charges for work performed other than during normal business hours. Damage incurred in transit or from installation error, accident, alteration or misuse is not covered. Univex shall not be liable for any consequential compensatory, incidental, or special damages. Contact the Univex service department for any warranty claims.



Univex Corporation
www.Univexcorp.com

3 Old Rockingham Rd
Salem, NH 03079
United States of America

Telephone (800) 258-6358
Intl Tel. (603) 8936191
Fax (800) 356-5614
Intl Fax (603) 8931249



Exacting Standards, Just Like yours, since 1948

SILVERLINE Spiral Mixer

SL50 / SL60 Plus / SL80 / SL120

Dimensions:



	SL50	SL60	SL80	SL120
A:	20.9" (530mm)	27.6" (700mm)	27.6" (700mm)	30.7" (780mm)
B:	36.2" (920mm)	44.1" (1120mm)	44.1" (1120mm)	53.9" (1370mm)
C:	44.9" (1140mm)	49.2" (1250mm)	49.2" (1250mm)	57.1" (1450mm)
D:	59.1" (1500mm)	74.8" (1900mm)	74.8" (1900mm)	76.8" (1950mm)

- A:** Total mixer width including bowl diameter.
- B:** Total mixer depth
- C:** Mixer Height
- D:** Mixer height including safety guard/lid fully open

Motor:

Spiral:

SL50: 3.5HP, 17.45A, 2.6KW
SL60Plus: 6HP, 27.25A, 4.5KW
SL80: 6HP, 27.25A, 4.5KW
SL120: 8HP, 31.68A, 6.1KW

Bowl:

SL50: .75HP, 2.7A, .55KW
SL60Plus: .75HP, 2.7A, .55KW
SL80: .75HP, 2.7A, .55KW
SL120: 1HP, 3.6A, .75KW

Electrical: 220V/60Hz/3P

(Contact factory for alternate voltages)

Controls: Control panel with digital timers.

Separate timers for high and low speed.

Security key for manual use. Bowl reverse direction switch.

Transmission: Heavy duty low noise and low vibration belt drive

Bowl Guard: Swings open for full access to bowl. Guard must be closed for mixer operation

Shipping Information:

	SL50	SL60Plus	SL80	SL120
Freight Class:	85	85	85	85
Net Weight:	474lb (215kg)	7.5lb (320kg)	728lb (330kg)	1080lb (490kg)
Shipping Weight:	548lb (265kg)	816lb (370kg)	838lb (380kg)	1190lb (540kg)

Shipping Information:

	SL50	SL60Plus	SL80	SL120
Height:	59"(1500mm)	67" (1700mm)	67"(1700mm)	67.3"(1710mm)
Width:	31"(787mm)	31" (787mm)	31"(800mm)	32.7"(830mm)
Depth:	32"(820mm)	50" (1260mm)	50"(1260mm)	53"(1350mm)
Cubic Measure:	50:33.9ft ³ (.95M ³)	60: 60.5ft ³ (1.71M ³)	80: 60.5ft ³ (1.71M ³)	120: 67.7ft ³ (1.92M ³)



Univex Corporation
www.Univexcorp.com

3 Old Rockingham Rd
 Salem, NH 03079
 United States of America

Telephone (800) 258-6358
 Intl Tel. (603) 8936191
 Fax (800) 356-5614
 Intl Fax (603) 8931249