

#### WE RAISE THE BAR. WE SET THE STANDARD.

Item Number **Project** Quantity

# 4612 **Economy Slicer**

#### Model:

> 4612: 1/4hp Manual Slicer





CERTIFIED BY NSF INTERNATIONAL TO MEET AND EXCEED THE NSF/ANSI 2012 STANDARDS

#### Features:

**Economy Series Slicer** 

Univex Corporation

- Light duty, intermediate volume slicer
- Maximum duty 2 hours a day
- Capable of slicing small amounts of cheese
- Unique drip tray fence redirects liquids away from controls and operator towards distinctive concave base casting for easy cleaning
- Ergonomic comfort design operation
- Powerful 1/4 hp motor standard
- Adjustable slice thickness from 0 to 1/2"
- Easily removable sharpener for cleaning
- Quick and simple disassembly of carriage and feed grip for easy and thorough cleaning
- Sanitary polished and anodized aluminum construction
- Permanantly mounted protective edge guard for operator safety

12" Precision slicing German hollow ground blade Unique smooth curve transitions to redirect liquids away from controls and operator Easily detachable carriage for easy cleaning

### **Optional Accessories:**

- Stainless steel blade
- Heavy duty clear plastic cover

## Warranty:

• One year, carry-in parts and labor



**Univex Corporation** www.Univexcorp.com


3 Old Rockingham Rd Salem, NH 03079 United States of America


TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249




# **Economy Series Slicer**

4612







Controls: Manual slice thickness knob, push button on/off,

attached blade sharpener

Drive Assembly: Belt driven

Blade diameter: 12" (38.48cm) razor sharp blade

Blade RPM: 420 RPM

Maximum slice thickness: .5" (1.27cm)

Maximum product size: Rectangular:  $8" \times 5"$  (20.3cm × 13.3cm)

Square:  $5" \times 5"$  (13.3cm x 13.3cm)

Round: 7" (20.3cm)

Construction: Anodized, cast aluminum body for durability

and stunning looks

Nema #: 5-15-P

Electrical Information (60Hz)						
	Voltage	Phase	Amps	RPM	hp(kW)	
Standard Voltage	115	1	1.9	1680	1/4 (.19)	
Optional Voltage	208-240	1	1.0	1680	1/4 (.19)	

Carriage Stroke
9.25" (23.5cm)

Shipping Information				
Net Weight	Shipping Weight	Overall Shipping Dimensions		
50.6lbs. (23Kg) 59lbs. (26.8Kg)		21" (53.3cm) H x 27" (68.6cm) W x 23" (58.4cm) D		



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249