

MG8912

Meat and Food Grinder

Univex Corporation

## WE RAISE THE BAR. WE SET THE STANDARD

Item Number **Project** Quantity

# **Duty Level**



# **Meat and Food Grinder** with #12 Hub

### MADE IN THE USA

## Model:

MG8912: 1hp meat and food grinder





• 12"x20" (30.5cmx50.8cm) stainless steel feed pan

## **Features:**

- Medium duty meat and food grinder
- Grinds 8 to 12 lbs. per minute on first grind with a 3/16" (0.5cm) plate
- 1 hp motor with 1" (2.5cm) poly V belt drive
- Compact but powerful design
- Perfect for small schools, nursing homes, and restaurants
- Comes ready to grind with a 3/16" grind plate, X-knife, stainless steel feed pan, and aluminum stomper

#### • 3/16" (0.5cm) grind plate • 1/4" (0.6cm) grind plate

- 1/8" (0.3cm) grind plate

**Optional Accessories:** 

**Standard Accessories:** 

• 3/16" (0.5cm) grind plate

Aluminum stomper

- 3/8" (1cm) grind plate
- 1/2" (1.3cm) grind plate
- X-knife

X-knife

- 1/2" (1.3cm) stuffing tube
- 3/4" (1.9cm) stuffing tube
- Small plastic cover

## **Warranty:**

One year, on-site parts and labor



**Univex Corporation** www.Univexcorp.com 3 Old Rockingham Rd Salem, NH 03079 United States of America


TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249


Printed in U.S.A. 01/2017 REV 1 LH-980




# **Meat and Food Grinder**

MG8912







Motor: 1 hp capacitor start, 1740RPM, ball bearing motor mounted on cushioned supports for noise and vibration reduction.

Drive: 7:1 reduction produces increased torque. Uses a ribbed poly-V belt, 266RPM drive shaft supported by ball bearings in PTO.

Drive Assembly: Completely enclosed in a powder coated ten gauge stainless steel cover and a powder coated steel cover.

Switch: Rocker type double pole on/off conveniently located on the front side of the machine. Has a removable key to lock out machine.

Meat Grinder: Aluminum housing with No.12 tapered hub. Housing is locked into the drive assembly, PTO housing, by a thumbscrew. Grinder housing has internal spiral flutes designed to shear and force product through the hardened steel knife.

Feed Pan: 8.3 quarts (7.9 liters).  $12"\times20"$  (30.5 x 50.8cm)

Feed Stomper: Aluminum stomper designed for ease of use and safety.

NEMA #: 5-15-P

Electrical Information (60Hz)					
	Voltage	Phase	hp(kW)	Amps	
Standard Voltage	115	1	1 (0.75)	9	
Optional Voltage	208-230	1	1 (0.75)	4.5	

Shipping Information			
Net Weight	Shipping Weight	Overall Dimensions	
99 lbs. (44.9Kg)	108 lbs. (49Kg)	24" (61cm) H x 18" (45.7cm) W x 25" (63.5cm) D	



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249