

WE RAISE THE BAR. WE SET THE STANDARD.

Item Number **Project** Quantity

PM91 - PM91G #12 Hub Power Drive Unit

Prep-Mate™ **Power Drive Unit**

MADE IN THE USA

Models:

- PM91: #12 POWER DRIVE UNIT
- PM91G: #12 POWER DRIVE UNIT WITH EXTENDED LEGS





Features:

- 1 HP motor
- Power base will drive any accessories made for the #12 power take off (PTO) hub.
- Runs attachments at 250rpm.
- On/off switch has removable operator key to prevent unauthorized operation.
- Comes with a 5 inch deep prep container with cover
- PM91G has all the above features but also features extended legs to allow you to use a larger prep container.

Standard Accessories:

• 5" deep prep container with cover.

Optional Accessories

- VS9 vegetable slicer attachment
- VS9H grater/shredder attachment
- ALMFC12 meat and food grinder
- 1000450 plastic cover

Warranty:

One year, on-site parts and labor

Unit is a power drive unit only see back of spec sheet for the different optional #12 attachments.



Univex Corporation

Univex Corporation www.Univexcorp.com 3 Old Rockingham Rd Salem, NH 03079 United States of America

TEL: 800.258.6358 INTL TEL: 603.893.6191 FAX: 800.356.5614 INTL FAX: 603.893.1249





Prep-Mate™ Power Base

PM91/PM91G



4 10.5" (267mm) ► Width of Just Power Unit







ALMFC12 meat and food grinder

Comes with housing, worm, rimg, feed pan, stomper, 3/16" (5mm) plate and X-knife. See spec sheet for more details.



VS9 vegetable slicer attachment

Comes with housing & adjustable "S" knife assembly. Use for slicing carrots, lettuce, cucumbers, celery, and other vegatables.



VS9H grater/shredder attachment

Comes with housing, hub and shaft, and a 3/16" (5mm) shredding plate. Use with cheese, cole slaw, or bread crumbs. See spec sheet for more plate options.

Motor: 1 hp capacitor start, 1740rpm, ball bearing motor with cushioned mounts to reduce vibration &

Drive: 7:1 reduction increases torgue, ribbed poly-V belt, 266 rpm drive shaft supported by ball bearings in the PTO housing.

Drive Assembly: Completely enclosed in a powder coat finished 10 gauge steel housing finished steel cover.

Switch: Rocker-type double-pole on/off switch located access from the front or left side of unit. Also features a removable key to stop unathorized use of machine.



Electrical Information (60Hz)			
	Voltage	Phase	Amps
Standard Voltage	115	1	11.5





Shipping Information			
Net Weight	Shipping Weight	Overall Dimensions	
82 lbs. (37.2Kg)	92 lbs. (42 Kg)	24"(610mm) H X 19" (483mm) W X 26" (660mm) D	



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: 800.258.6358 INTL TEL: 603.893.6191 FAX: 800.356.5614 INTL FAX: 603.893.1249