

SFG500B

Dough Sheeter

Univex Corporation

WE RAISE THE BAR. WE SET THE STANDARD.

Project Item Number Quantity

Reversible Bench Top Dough Sheeter



Model:

> SFG500B: Bench Model





Features:

- Reversible bench top dough sheeter
- 0 to 1.9" (4.8cm) adjustable cylinder, separation changes dough thickness
- Hard chrome polished cylinders
- Tables fold upright for storage and movement
- Powerful 3/4 hp motor
- Sheets dough onto rolling pins to allow for transport of rolled dough to work area
- Interlock switches protect operator from injury if safety guard is opened
- Pivoting and removable arms

Standard Accessories:

- Heavy duty rolling pins
- Designated area for flour storage for use while sheeting

Warranty:

One year, on-site parts and labor




Univex Corporation www.Univexcorp.com


3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249





Reversible Bench Top Dough Sheeter

SFG500B









The Dimensions from edge of foot, to edge of foot are 25" long by 10" wide.

	Other Dimensions				
Base Length	Belt Width	Length Folded	Height Folded	Carpet Length	Leg Width
11.875" (30.2cm)	19.75" (50.2cm)	29.625" (75.25cm)	32.5" (82.6cm)	27.625" (70.2cm)	44.875"(113.9cm)

Controls: Main power switch, emergency stop switch and direction control lever for forward and reverse table directions. Manually adjustable space between rolling cylinders adjusts in increments from 0" to 1.9" (0 to 4.8cm)

Drive: Chain drive Optional Voltages:

220/60/1

NEMA #: L-15-20

Electrical Information (60Hz)				
Standard Voltage	Phase	hp(kW)	Amps	
		0.75 (0.55)	0 10 7 05	

Shipping Information				
Net Weight	Shipping Weight	Overall Dimensions		
312 lbs. (142Kg)	423 lbs. (192Kg)	36" (91.4cm) H x 52" (132.1cm) W x 35" (88.9cm) D		



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249