SRM60+PM

Floor Model Mixer

Univex Corporation

Project Item Number Quantity

(in) ivex

Features:

• 3 hp capacitor start motor

*Shown with optional PTO

- Variable Speed Drive: 2 fixed speeds
- Change speeds without having to stop the mixer
- Two-piece, stainless steel, dishwasher safe safety guard
- Heavy-duty stainless steel bowl
- #12 Power Take-Off (PTO) hub
- Interlock switches protect operator from injury if safety guard is open or bowl is lowered
- Hardened alloy gears in transmission
- Low voltage protection prevents accidental start up after power failure
- Durable NSF approved hybrid epoxy/ polyester powder coat finish

60 Quart (qt.) Floor Model Pizza Mixer with Dough Hook Only

MADE IN THE USA

Model:

> SRM60+PM: 60 qt. FLOOR MODEL PIZZA MIXER WITH DOUGH HOOK ONLY





Standard Accessories:

- 15 minute timer
- 60 qt. stainless steel bowl
- Dough hook

Optional Accessories:

- Splash ring
- Cover
- Sweet dough beater
- Wire whip

- Ingredient chute
- Power bowl lift
- 60 qt. pastry knife
- Four wing beater
- Bowl truck
- Batter beater

Optional Attachments:

- VS9 vegetable slicer with adjustable knife
- VS9H vegetable shredder with plate holder and 3/16" plate (additional plate size variations, grater plates, and julienne plate available)
- ALMFC12 meat and food grinder

Warranty:

Two year, on-site parts and labor




Univex Corporation www.Univexcorp.com


3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249




60 Quart Floor Model Pizza Mixer

SRM60+PM







^{*}Shown with optional PTO

Shipping Information						
Net Weight	Shipping Weight	Overall Dimensions	Cubic Measure			
835 lbs. (378.7Kg)	1000 lbs. (453.6Kg)	66" (167.6cm) H x 41" (104.1cm) W x 51" (129.5cm) D	79.9ft.3 (2.26M3)			
*The weight and dimensions of the pallet are included in the weight and dimensions above.						

NEMA #: 6-20-P

Electrical Information (60Hz)					
Attached 6 foot cord	Voltage	Phase	Amps		
Standard Voltage	208-240	1	16.0-16.8		
Optional Voltage	208-240	3	8.0-8.5		
Opiloliai vollage	400	3	4.0		

Mixer Speeds					
Speed	1	2			
Beater Shaft (RPM)	90	166			
PTO (RPM)	90	163			

Bowl Capacity: 64 qts. (60.5 liters)

Motor: 3 hp capacitor start

Controls: Momentary contact stop & start buttons

and contactor magnetic starter with overload protection

Bowl Lift: Ergonomic hand operated crank, self locking

in top and bottom position

Lubrication: Oil bath

Transmission: Featuring hardened alloy gearing and

torque sensing variable speed pulleys



Univex Corporation www.Univexcorp.com

3 Old Rockingham Rd Salem, NH 03079 United States of America TEL: (800)258-6358 INTL TEL: (603)893-6191 FAX: (800)356-5614 INTL FAX: (603)893-1249